

18AWG 4 CONDUCTOR PLENUM RATED (SHIELDED)



SKU: 211-184/S/P/WH

COLOR CODE: Black, Red, White, Green, Brown, Blue, Orange, Yellow, Violet, Gray, Pink, Beige

SHIELD/DRAIN: Overall - Aluminum foil, polyester reinforced tape and stranded tinned copper drain wire

ASSEMBLY: 4 conductors twisted, shielded and jacketed

JACKET: LS-PVC
DIAMETER: 0.184" Nominal
CABLE WT: 34 Lbs/1000 Ft Approx (Net Weight)

NEC: CMP/CL3P

COMPLIANCE: UL 444 CMP by (UL) / NEC ARTICLE 800 / CSA C22.2 by c(UL) / RoHS

FLAME TEST: NFPA 262(UL 910) / CSA FT6
CAPACITANCE: 46.8 pF/Ft Nominal
VEL OF PROP: 55%
IMPEDANCE: 39 OHMS
RESISTANCE: 6.92 OHMS D.C. PER 1000 Ft @ 68 DEG. F Maximum
TEMP/VOLTAGE: 75C / 300V

COMPLIANCE:

UL 444 CMP by (UL) / NEC ARTICLE 800 / CSA C22.2 by (UL), RoHS Compliant

MARKING ON JACKET:

3122598 CMP/FPLP 18AWG c(ETL)US FT6 Made in USA WO-061088

FOOTAGE MARKS: FOOTMARK IN ASCENDING ORDER

DESCRIPTION

18/4 Stranded Bare Copper Conductors, Shielded with an overall jacket, 1000ft Spool, CMP/CL3P

FEATURES

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- UL Listed to UL444 and UL13, RoHS
- 1000ft Spool

VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York



www.verticalcable.com

Rev. 4/2019

Specs subject to change without notice.
It is the sole responsibility of the user to have the most current specs.