


### **DESCRIPTION**

22/6 Stranded Bare Copper Conductors, Shielded with an overall jacket. Plenum Rated, 1000ft Pull Box

#### **FEATURES**

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Supplied in a 1000ft Pull Box



# 22AWG 4 CONDUCTOR SHIELDED PLENUM RATED

## SKU: 210-226/S/P/WH

**Conductor** 

Material Bare Copper Size 22AWG

Stranding 7 Strand (7x0.01in., 7x0.254mm)

Conductors 6 Conductor

Shielding Aluminum Foil

Drain Wire 24AWG Strand Tinned

Copper

Insulation

Material PL-PVC

Colors Black, Red, White, Green,

Brown, Blue

Ripcord Yes

**Jacket** 

Material PL-PVC

Overall Diameter 0.155 in. Nominal

Color White

**Electrical Properties** 

Temp. Rating  $-20^{\circ}\text{C} \sim +75^{\circ}\text{C}$ 

DCR Conductor 55.4 Ohms/Km. @ 20°C DCR Drain Wire 90.9 Ohms/Km. @ 20°C

Ratings/Approvals

NEC Article 800, UL Subject 444, CMP/CL2P (UL), RoHS

Compliant







### **VERTICAL CABLE**

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York