

# BNC CONNECTOR

## COMPRESSION TYPE

### For RG59 Plenum Coax Cable



**SKU: 083-1045/PCPBNC**

## DESCRIPTION

BNC Compression Type Connector.  
Compatible with most RG59 plenum cable.

## FEATURES

- BNC connector for RG59 plenum cable
- Red plastic identifier ring
- Suitable for CCTV applications
- 100 pcs per bag

## TOOLS



Compression/Crimping Tool  
078-1018



Universal Stripping Tool  
078-1022

### Physical Properties

- Nut and Collar: NiTin Plated Brass
- Split Ferrule Body: Tin Plated Brass

### Electrical Properties

- Return Loss: > -30 dB up to 1 GHz typical
- Insertion Loss: < -0.2 dB up to 1 GHz typical
- RFI Shielding: -85 dB typical (60% bonded foil)

### Mechanical Properties

- Cable Insertion Force: 20 lbs. maximum
- Cable Retention Force: 40 lbs. minimum per SCTE IPS-SP-401

### Environmental Properties

- Temperature Rating -40 °F (-40 °C) to 140 °F (60 °C)
- Salt Fog: Passes 1000 hours ANSI/SCTE 143 2007

#### Cable sizes:

Inches	Minimum ~ Maximum
Center	.0317 ~ .0339
Dielectric	.130 ~ .157
Outer Jacket	.190 ~ .220



## VERTICAL CABLE

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York

[www.verticalcable.com](http://www.verticalcable.com)

Rev. 06/2017

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.