


DESCRIPTION

18AWG, 2 Conductor, Stranded Bare Copper (7 Strand), PVC Jacket Pull Box, 1000FT, Made in USA

APPLICATION

- **Intercom Systems**
- **Security Systems**
- **Burglar Alarms**
- **Sound Systems**
- **Power Limited Control Circuits**
- **Indoor Applications**
- CL3R, CMR (Riser Rated)



18AWG 2 CONDUCTOR STRANDED (7 STRAND) SHIELDED - RISER RATED

SKU: 309-3074/S/WH (white) 309-3073/S/GY (gray)

Conductor

Product Description

2 Core (Stranded) Polyvinyl Chloride (PVC) insulated bare copper

conductors jacketed will an overall PVC jacket. Shielded.

Size 18 AWG Stranding CAP (pF/FT) 54

Shield Low Smoke Aluminum Mylar Drain Wire 24 AWG Tinned Copper

Insulation

Material **PVC**

Thickness 0.009" (0.23mm)

Colors Black, Red, White, Green, Brown, Blue

Jacket

PVC Material

Thickness 0.015" (0.38mm) Nominal Outer Diameter 0.165" (4.19mm)

Ripcord

Material High Strength Polyester

Electrical Performance

Rated Temperature -25C° to 75C° 300 Volt Voltage Rating

NEC Articles CMP (UL444) NEC 800 CL3P (UL13) NEC 72

Marking on Jacket

4010346 18 AWG 2 COND. RISER SHIELDED STRANDED 75C CMR c(ETL)us FT4 CL3R ROHS COMPLIANT MADE IN USA PO##### OPER### CL## [####FT/ ###FT]

SEQUENTIAL FOOT MARKERS ON JACKET

Approximate shipping weight: 22LBS White generic pull box (10"x13.5"(h)x14.5"



951.696.7772 California 800.749.2447 Florida 845.391.8318 New York







