

COMPONENTS & ACCESSORIES

Splicing OSP Splice Closures



	265-OSC00-09606	265-OSC00-09608	265-OSC00-24006
Horizontal, In-line			
Fiber capacity	96	96	240
Cable entry ports	6	8	6
Splice cassettes	8 × 12F	8 × 12F	20 × 12F
Cable diameter range	8 mm–23 mm (0.32 in–0.91 in)		
Dimensions	450 mm × 220 mm × 110 mm (17.7 in × 8.7 in × 4.3 in)		450 mm × 220 mm × 160 mm (17.7 in × 8.7 in × 6.3 in)
Weight*	2.75 kg–3.2 kg (6.1 lb–7.1 lb)		3.1 kg–3.8 kg (6.8 lb–8.4 lb)
Material	High-impact fiber-reinforced PC		
Environmental protection	IP68		
Radiation protection	UV resistant		
Operating temperature	-40 °C–+65 °C (-40 °F–+149 °F)		

	265-OSC10-09602	265-OSC10-04804	265-OSC10-28806
Vertical, Dome			
Fiber capacity	96	48	288
Cable entry ports	2	4	6
Splice cassettes	8 × 12F	4 × 12F	24 × 12F
Cable diameter range	7 mm–14 mm (0.28 in–0.55 in)	8 mm–16 mm (0.32 in–0.63 in)	8 mm–21 mm (0.32 in–0.83 in)
Dimensions	280 mm × 200 mm × 90 mm (11.0 in × 7.9 in × 3.5 in)	290 mm × 180 mm (11.4 in × 7.1 in)	455 mm × 220 mm (17.9 in × 8.7 in)
Weight*	1.2 kg–1.5 kg (2.7 lb–3.3 lb)	1.8 kg–1.9 kg (4.0 lb–4.2 lb)	3.3 kg–4.2 kg (7.3 lb–9.3 lb)
Material	High-impact fiber-reinforced PC		
Environmental protection	IP68		
Radiation protection	UV resistant		
Operating temperature	-40 °C–+65 °C (-40 °F–+149 °F)		

* Weight range is given depending on the number of splice cassettes installed, none to maximum.