

Splicing

Splice Trays – Compact

265-CAS01-1n2xy Optical fiber splice tray, compact, stackable, (stack of "n"), 24-fiber, ("x" protection sleeves per tray), black

Substitute "n" in PN with:

"B": single tray;
 "2": 2-stack;
 "3": 3-stack;
 "4": 4-stack;
 "5": 5-stack;
 "6": 6-stack.

Substitute "x" in PN with:

"O": no sleeves;
 "A": 2 sleeves;
 "B": 4 sleeves;
 "C": 6 sleeves;
 "D": 8 sleeves;
 "E": 12 sleeves;
 "F": 24 sleeves.

Substitute "y" in PN with:

"O": no sleeves;
 "A": 40-mm sleeves.



265-CAS01-1 splice trays are supplied with two splice holders and custom number of 40-mm 265-SLV01-3A splice sleeves.

PN example: 265-CAS01-122EA Optical fiber splice tray, compact, 2-stack, 12 × 40-mm sleeves per tray.

Splice Trays – Standard

265-CAS01-2n2xy Optical fiber splice tray, standard, stackable, (stack of "n"), 24-fiber, ("x" protection sleeves per tray), transparent cover, black

Substitute "n" in PN with:

"B": single tray;
 "2": 2-stack;
 "3": 3-stack;
 "4": 4-stack;
 "5": 5-stack;
 "6": 6-stack.

Substitute "x" in PN with:

"O": no sleeves;
 "A": 2 sleeves;
 "B": 4 sleeves;
 "C": 6 sleeves;
 "D": 8 sleeves;
 "E": 12 sleeves;
 "F": 24 sleeves.

Substitute "y" in PN with:

"O": no sleeves;
 "A": 40-mm sleeves;
 "B": 60-mm sleeves.



265-CAS01-2 splice trays are supplied with two splice holders and custom number of 40-mm 265-SLV01-3A or 60-mm 265-SLV01-3B splice sleeves.

PN example: 265-CAS01-2B2FB Optical fiber splice tray, standard, single, 24 × 60-mm sleeves.

CHARACTERISTICS

Compatible splicing: fusion splice, heat-shrink protection sleeves.

Capacity: 265-CAS01-1n2: 24 fibers (24 265-CAS01-1B2 sleeves);
 265-CAS01-2n2: 24 fibers (24 265-CAS01-1B2 or 265-CAS01-2B2 sleeves).

Features: 265-CAS01-1n2: two splice holders;
 fiber-management and slack storage mechanism;

Splicing

Splice Trays – Compact

	265-CAS01-2n2	cable anchoring points; vertically stackable. two splice holders; fiber-management and slack storage mechanism; cable anchoring points; vertically stackable; transparent cover; administration ID label.
Materials:	body: splice holder:	ABS (acrylonitrile butadiene styrene); PP (polypropylene).
Accessories:	2 white nylon cable ties; 4 double-sided adhesive pads; 2 sets of mounting machine screws, nuts, spacers (hardware units with 45-mm and 145-mm ctc mounting points).	
Environmental:	operating temperature: -20 °C–+70 °C (-4 °F–+158 °F); operating humidity: ≤95 % RH non-condensing.	
Dimensions:	265-CAS01-1B200:	140 mm × 100 mm × 12 mm (5.5 in × 4.0 in × 0.5 in);
	265-CAS01-2B200:	225 mm × 105 mm × 12 mm (8.9 in × 4.1 in × 0.5 in).
Weight:	265-CAS01-1B200: 265-CAS01-2B200:	
Compliance:	Telcordia GR-771-CORE; RoHS.	
Compatibility:	265-CAS01-1n2:	VC _{fiber} 267-RES, 267-REB, 268-STD, 268-EZX, 268-EZV Series
	265-CAS01-2n2:	VC _{fiber} 267-RES, 267-REB Series