

## COMPONENTS AND ACCESSORIES



### Splicing

#### Splice Holders

265-HLD01-2B-xy Optical fiber splice holder, adhesive mounting, two fibers per slot, six slots, twelve fibers

Substitute "x" in PN with: Substitute "y" in PN with:

"O": no sleeves;	"O": no sleeves;
"A": 2 sleeves;	"A": 40-mm sleeves;
"B": 4 sleeves;	"B": 60-mm sleeves.
"C": 6 sleeves;	
"D": 8 sleeves;	
"E": 12 sleeves.	



PN example: 265-HLD01-2B-00 Optical fiber splice holder, adhesive mounting, no sleeves.

PN example: 265-HLD01-2B-EB Optical fiber splice holder, adhesive mounting, twelve 60-mm sleeves.

#### CHARACTERISTICS

Compatible splices:	fusion splice, heat-shrink protection sleeves.
Capacity:	6 slots × 2 fibers/slot = 12 fibers.
Material:	PP (polypropylene).
Color:	black.
Mounting type:	adhesive pad.
Environmental:	operating temperature: -20 °C–+70 °C (-4 °F–+158 °F); operating humidity: ≤95 % RH non-condensing.
Dimensions:	40 mm × 30 mm × 7 mm (1.6 in × 1.2 in × 0.3 in).
Weight:	2.5 g (0.09 oz);
Compliance:	ANSI/UL 94 V-2.



265-HLD01-2B-EB