

Splice Protection Sleeves

265-SLV01-3A-n Optical fiber splice protection sleeve, 2.5 mm × 40 mm, pack of “n”

265-SLV01-3B-n Optical fiber splice protection sleeve, 2.5 mm × 60 mm, pack of “n”

Substitute “n” in PN with:

“E”: 12 sleeves;

“F”: 24 sleeves;

“G”: 48 sleeves;

“H”: 96 sleeves.

**CHARACTERISTICS**

Diameter:	external tubing:	2.5±0.3 mm (0.1±0.01 in) after shrinking;
	internal tubing:	1.3±0.1 mm (0.05±0.01 in);
	rod:	1.2±0.05 mm (0.05±0.002 in).
Length:	265-SLV01-3A:	overall: 40±2 mm (1.6±0.08 in);
		rod: 34±2 mm (1.3±0.08 in);
	265-SLV01-3B:	overall: 60±2 mm (2.4±0.08 in);
		rod: 54±2 mm (2.1±0.08 in).
Materials:	external tubing:	polyolefin (PAO);
	internal tubing:	ethylene-vinyl acetate (EVA);
	rod:	stainless steel.
Shrinking temperature:	≥100 °C (212 °F).	
Weight:	265-SLV01-3A:	0.40 g (0.014 oz);
	265-SLV01-3B:	0.65 g (0.023 oz).
Packing:	re-closable plain PE bags.	