



| OSP Tension Clamps | 269-OPH02-80702 | 269-OPH02-80902 | 269-OPH02-D10P7 | 269-OPH02-D11P2 |
|------------------------------|---|--------------------------------|---|-------------------------------|
| |  | |  | |
| Cable construction: | Self-supporting drop "8 in, fiber-reinforced plastic (FRP) or aramid yarn messenger | | FTTH drop | |
| Cable/messenger OD diameter: | 3 mm–7 mm (0.12 in–0.3 in) | 6 mm–9 mm (0.25 in–0.35 in) | 3 mm–5 mm (0.12 in–0.2 in) | 3 mm–7 mm (0.12 in–0.3 in) |
| Load capacity: | 2 kN (~450 lbf) | | 0.7 kN (~160 lbf) | 1.2 kN (~270 lbf) |
| Cable retention mechanism: | Tension, self-adjusting wedges | | Tension, wedge, and perforated shim | |
| Material: | Fiberglass-reinforced plastic | | Stainless steel Type 201 | |
| Length: | — | — | 150 mm (8.7 in) | 220 mm (8.7 in) |
| Bail material: | Stainless steel | | | |
| Bail length: | 230 mm (9 in) | | | |
| Operating temperature: | -60 °C–+60 °C (-76 °F–+140 °F) | | | |
| Mounting: | Wall or pole using clamp anchor points (brackets) | | | |
| Applications: | Dead-end support/drop | | | |

| OSP Brackets | 269-OPH10-0115 | 269-OPH10-0304 |
|----------------|---|---|
| |  |  |
| Load capacity: | 15 kN (~3,370 lbf) | 5 kN (~1,120 lbf) |
| Material: | Aluminum alloy | |
| Dimensions: | 116 mm × 35 mm × 20 mm (4.6 in × 1.4 in × 0.8 in) | 120 mm × 100 mm × 50 mm (4.7 in × 4 in × 2 in) |
| Mounting: | Wood, concrete, metal poles Steel bands or bolts | |
| Applications: | Anchor point for clamps (single/double) | Anchor point for clamps Horizontal support: up to 3 clamps Drop: up to 5 clamps |

| OSP Hooks | 269-OPH30-011P5 |
|----------------|--|
| |  |
| Load capacity: | 1.5 kN (~340 lbf) |
| Material: | Galvanized steel |
| Dimensions: | 65 mm × 65 mm × 55 mm (4.6 in × 1.4 in × 0.8 in) |
| Mounting: | Wood, concrete, metal poles Steel bands or screws |
| Applications: | Anchor point for clamps |