

# CROSS-CONNECT ► Rack-Mount Identification and Labelling

## ZERO-U Administration Panels



- 266-LBL00-A0A1A Administration Panel, Zero-U, Rack-Mount, Quarter Label Holders x1
- 266-LBL00-A0A2A Administration Panel, Zero-U, Rack-Mount, Quarter Label Holders x2
- 266-LBL00-A0A3A Administration Panel, Zero-U, Rack-Mount, Quarter Label Holders x3
- 266-LBL00-A0A4A Administration Panel, Zero-U, Rack-Mount, Quarter Label Holders x4\*



- 266-LBL00-A0A1B Administration Panel, Zero-U, Rack-Mount, Third Label Holders x1
- 266-LBL00-A0A2B Administration Panel, Zero-U, Rack-Mount, Third Label Holders x2
- 266-LBL00-A0A3B Administration Panel, Zero-U, Rack-Mount, Third Label Holders x3\*



- 266-LBL00-A1A1A Administration Panel, Zero-U, Panel-Mount, Quarter Label Holders x1
- 266-LBL00-A1A2A Administration Panel, Zero-U, Panel-Mount, Quarter Label Holders x2
- 266-LBL00-A1A3A Administration Panel, Zero-U, Panel-Mount, Quarter Label Holders x3
- 266-LBL00-A1A4A Administration Panel, Zero-U, Panel-Mount, Quarter Label Holders x4\*



- 266-LBL00-A1A1B Administration Panel, Zero-U, Panel-Mount, Third Label Holders x1
- 266-LBL00-A1A2B Administration Panel, Zero-U, Panel-Mount, Third Label Holders x2
- 266-LBL00-A1A3B Administration Panel, Zero-U, Panel-Mount, Third Label Holders x3\*



\* Panels with three third label holders and four quarter label holders that occupy whole identification area are supplied with label holders affixed to panels. All other configurations are supplied with label holders as separate parts in order to facilitate adjusting their positions in the field per project requirements.



### MOUNTING DETAILS

RACK-MOUNT VERSION	PANEL-MOUNT VERSION
RACK-MOUNT VERSION JOINT MOUNTING WITH 266-CFM CMB	PANEL-MOUNT VERSION JOINT MOUNTING WITH 266-CFM CMB

## CHARACTERISTICS

Compatibility:	266-LBL00-A0	266-LBL00-A1
	Any equipment with rack mounting format meeting EIA-ECA-310-E 19-in standard specifications	VC fiber products equipped with T-anchor openings

Compliance: ANSI/TIA-606, ISO/IEC TR 14763-2-1.

Materials: panels: 1.5-mm (16-GA) CRS, black powder coating (RAL 9005, jet black);  
label holders: PVC, double-sided adhesive tape, plain paper label.

Rack mounting: above or below equipment unit being administered;  
screws used to mount equipment unit being administered, size range: M5–M6, #10–#12.

Panel mounting: integral spring-loaded snap-in T-anchors;  
labeling area located below unit being administered.

Label type: insert type, plain paper/cardstock strips.

Environmental: operating temperature: -20 °C–+70 °C (-4 °F–+158 °F);  
operating humidity: ≤95 % RH non-condensing.

Dimensions, panels:	266-LBL00-A0	266-LBL00-A1
Width, overall:	483 mm (19.0 in)	438 mm (17.2 in)
Width, labeling area:	419 mm (16.5 in)	
Height, overall:	19 mm (0.8 in)	34 mm (1.3 in)
Height, labeling area:	14 mm (0.6 in)	
Depth, overall:	13 mm (0.5 in)	18 mm (0.7 in)
Depth, panel:	10 mm (0.4 in)	15 mm (0.6 in)
Protrusion, overall:	13 mm (0.5 in)	
Weight:	120 g (4.2 oz)	
Dimensions, label holders:	Third label holders	Quarter label holders
Width, holder:	138 mm (5.4 in)	102 mm (4.0 in)
Height, holder:	14.2 mm (0.56 in)	
Width, label:	138 mm (5.4 in)	102 mm (4.0 in)
Height, label:	11 mm (0.43 in)	
Depth:	2.9 mm (0.11 in)	

## APPLICATION EXAMPLES

<p>ACTIVE EQUIPMENT PORT ADMINISTRATION</p> 	<p>UNITS WITH NO LABELING OPTIONS ADMINISTRATION</p> 
<p>SUPPORT INFRASTRUCTURE ADMINISTRATION</p> 	<p>UNITS WITH LIMITED LABELING OPTIONS ADMINISTRATION</p> 
<p>POWER DISTRIBUTION UNIT ADMINISTRATION</p> 	