

DESCRIPTION

22 AWG 4 Conductor Stranded Bare Copper, CL3P (Plenum Rated) Unshielded with an overall jacket.

APPLICATION

- Intercom Systems
- **Security Systems**
- **Sound and Audio**
- **Power Limited Control Circuits**
- **Indoor Applications**
- **Door Controllers**
- **Kev Pads**
- **Smoke Detectors**



ALARM-SECURITY CABLE

22 AWG 4 CONDUCTOR **PLENUM RATED, STRANDED**

210-224/P/WH

Part Number:	Description:
210-224/P/WH	Alarm-Security Cable, Plenum, Unshielded, Stranded, Bare Copper Conductors, 22 AWG 4 C, 1000 ft, White

CONSTRUCTION

Conductor count:

Stranding: 7 Strand 0.01 in. (0.25 mm)

Shape: Round Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

22 AWG Trade size:

Conductor O.D.: 0.02 in. (0.61 mm)

Insulation material: Polyvinyl Chloride (PVC) Insulation O.D.: 0.04 in. (0.96 mm)

Black, Red, White, Green Insulation color:

JACKET

Material: Polyvinyl Chloride (PVC) 0.02 in. (0.52 mm) Thickness: 0.14 in. (3.75 mm) O.D.:

Marking: 22AWG 4C STRANDED c(ETL)us CMP 5024318 RoHS/FT6/CL3P 53207M0729101 00:40 1000FT

MECHANICAL

Temperature rating: 75° C


SAFETY

DCR Conductor: 55.4 Ohm/Km. @ 20° C

CMP/CL3P NFPA 70 (NEC®) rating: 300 V RMS Voltage rating:

PACKED WEIGHT

210-224/P/WH 25 lb (11.3 kg)





951.696.7772 California 800.749.2447 Florida 845.391.8318 New York



