

DESCRIPTION

22 AWG 4 Conductor Solid Bare Copper, Shielded with an overall jacket.

APPLICATION

- Intercom Systems
- **Security Systems**
- Sound and Audio
- **Power Limited Control Circuits**
- **Indoor Applications**
- **Door Controllers** •
- **Kev Pads**
- **Smoke Detectors**





VERTICAL CABLE 951.696.7772 California 800.749.2447 Florida 845.391.8318 New York

ALARM-SECURITY CABLE 22 AWG 4 CONDUCTOR SOLID CONDUCTORS (SHIELDED)

210-224S0/S SERIES

Part Number:	Description:
210-224SO/S/5GY	Security Cable, Solid, Shielded, 22 AWG 4 C, Gray 500 ft.
210-224SO/S/WH	Security Cable, Solid, Shielded, 22 AWG 4 C, White 1000 ft.

CONSTRUCTION

Conductor count:		
Shape:		
Rip cord:		
Aluminum Foil:		
PE Tape:		
Drain Wire (TC)		
CONDUCTORS		

Round Yes Yes Yes 7/0.20

4

Bare solid copper 22 AWG 0.02 in. (0.61 mm) Polyvinyl Chloride (PVC) 0.04 in. (0.96 mm) Red, Black, White, Green

Polyvinyl Chloride (PVC)

0.02 in. (0.45 mm)

0.1 in. (3.40 mm)

JACKET

Material: Thickness: O.D.: Marking: VERTICAL 4001453 cETLUS CM/CL2 22AWG 4C

Material:

Trade size:

Conductor O.D.: Insulation material:

Insulation O.D.:

Insulation color:


SOLID SHIELDED 75C RoHS V1379P13404 XXXXFT

MECHANICAL

Temperature rating: SAFETY

> NFPA 70 (NEC®) rating: Voltage rating:

PACKED WEIGHT 210-224SO/S/5GY 210-224SO/S/WH



75° C

CM/CL2 300 V RMS

8 lb (3.6 kg) 15 lb (7.0 kg)



www.verticalcable.com

Rev. 10/2023 Subject to change without notice.