

ALARM-SECURITY CABLE

22 AWG 4 CONDUCTOR
STRANDED (SHIELDED)



210-224ST/S SERIES

Part Number:	Description:
210-224ST/S/WH	Security Cable, Stranded, Shielded, 22 AWG 4 C, 1000 ft, White
210-224ST/S/5WH	Security Cable, Stranded, Shielded, 22 AWG 4 C, 500 ft, White

CONSTRUCTION

Conductor count:	4
Shape:	Round
Rip cord:	Yes
PE Tape:	Yes
Drain Wire (TC):	Yes
Aluminum Foil:	Yes

CONDUCTORS

Material:	Stranded bare copper
Trade size:	22 AWG
Conductor O.D.:	0.02 in. (0.61 mm)
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.04 in. (1.10 mm)
Insulation color:	Red, Black, White, Green

JACKET

Material:	Polyvinyl Chloride (PVC)
Thickness:	0.02 in. (0.45 mm)
O.D.:	0.15 in. (3.80 mm)
Marking:	VERTICAL 4001453 cETLUS CM/CL2 22AWG 4C STRANDED SHIELDED 75C RoHS V1379P13404 XXXXFT

MECHANICAL


Temperature rating:	75° C
---------------------	-------

SAFETY

NFPA 70 (NEC®) rating:	CM/CL2
Voltage rating:	300 V RMS

PACKED WEIGHT

210-224ST/S/WH	19 lb (8.6 kg)
210-224ST/S/5WH	10 lb (4.5 kg)





DESCRIPTION

22 AWG 4 Conductor Stranded Bare Copper, CM/CL2, Shielded with an overall jacket.

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York



www.verticalcable.com

Rev. 10/2023

Subject to change without notice.