

ALARM-SECURITY CABLE

12 AWG 4 CONDUCTOR

STRANDED PLENUM RATED



211-124/P/5WH

Part Number:	Description:
211-124/P/5WH	Security Cable, Stranded, Plenum, 12 AWG 4 C, 500 ft, White

DESCRIPTION

12 AWG 4 Conductor Stranded Bare Copper, CL3P, Unshielded with an overall jacket.

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors

CONSTRUCTION

Conductor count: 4
Shape: Round
Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper
Trade size: 12 AWG
Stranding: 19 Strand
Strand Diameter: 0.02 in. (0.47 mm)
Insulation material: Polyvinyl Chloride (PVC)
Insulation O.D.: 0.04 in. (1.10 mm)
Insulation color: Red, Black, White, Green

JACKET

Material: Polyvinyl Chloride (PVC)
Thickness: 0.02 in. (0.46 mm)
O.D.: 0.31 in. (7.90 mm)
Marking: 12AWG*4C 75C 300V E499713 CMP (UL) C(UL) OR E507553 CL2P&CL3P (UL) 10/14/2021 RoHS COMPLIANT 0008FT

MECHANICAL



Temperature rating: 75° C
DCR Conductor: 5.41 Ohms/Km. @ 20°C

SAFETY

NFPA 70 (NEC®) rating: CMP/CL3P
Voltage rating: 300 V RMS

PACKED WEIGHT

Spool: 19.7 lb (8.9 kg)



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York



www.verticalcable.com

Rev. 10/2023
Subject to change without notice.