

ALARM-SECURITY CABLE

16 AWG 4 CONDUCTOR

STRANDED PLENUM RATED (SHIELDED)



211-164/S/P SERIES

| Part Number: | Description: |
|-----------------|--|
| 211-164/S/P/5WH | Security Cable, Stranded, Plenum, 16 AWG 4 C, 500 ft, White |
| 211-164/S/P/WH | Security Cable, Stranded, Plenum, 16 AWG 4 C, 1000 ft, White |

CONSTRUCTION

| | |
|------------------|-------|
| Conductor count: | 4 |
| Shape: | Round |
| Rip cord: | Yes |

CONDUCTORS

| | |
|----------------------|--------------------------|
| Material: | Stranded bare copper |
| Trade size: | 16 AWG |
| Stranding: | 19 Strand |
| Strand Diameter: | 0.02 in (0.47 mm) |
| Insulation material: | Polyvinyl Chloride (PVC) |
| Insulation O.D.: | 0.07 in. (1.90 mm) |
| Insulation color: | Red, Black, White, Green |

JACKET

| | |
|------------|---|
| Material: | Polyvinyl Chloride (PVC) |
| Thickness: | 0.01 in. (0.38 mm) |
| O.D.: | 0.20 in. (5.20 mm) |
| Marking: | 16AWG 4C STRANDED SHIELDED c(ETL)us CMP 5024318 RoHS/FT6/CL3P 52319M0729201 12:42 XXXXFT |

MECHANICAL

| | |
|---------------------|-------|
| Temperature rating: | 75° C |
|---------------------|-------|

SAFETY

| | |
|------------------------------|------------------|
| NFPA 70 (NEC®) rating: | CMP/CL3P |
| Voltage rating: | 300 V RMS |
| DC Resistance per Conductor: | @ 20° C 4.2Ω/1m' |
| Maximum pulling tension: | 168lbs |
| Min. Bend Radius: | 2vv .6 in |

PACKED WEIGHT




| | |
|------------------|--------------------|
| 211-164/S/P/5WH: | 25 lb (11.34 kg) |
| 211-164/S/P/WH: | 47.7 lb (21.64 kg) |

DESCRIPTION

16 AWG 4 Conductor Stranded Bare Copper, CL3P, Shielded with an overall jacket.

APPLICATION

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Door Controllers
- Key Pads
- Smoke Detectors



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York



www.verticalcable.com

Rev. 10/2023

Subject to change without notice.