

# AUDIO CABLE

## 14 AWG 4 CONDUCTOR

### STRANDED CABLE



## 209-2321 SERIES

Part Number:	Description:
209-2321	Audio Cable, Stranded, Unshielded, 14 AWG 4 C, White 500 ft.
209-2321/BK	Audio Cable, Stranded, Unshielded, 14 AWG 4 C, Black 500 ft.
209-2321/PR	Audio Cable, Stranded, Unshielded, 14 AWG 4 C, Purple 500 ft.

## DESCRIPTION

14 AWG 4 Conductor Stranded Bare Copper, Unshielded with an overall jacket.

### CONSTRUCTION

Conductor count: 4  
 Shape: Round  
 Rip cord: Yes

### CONDUCTORS

Material: Stranded bare copper  
 Trade size: 14 AWG  
 Stranding: 41/0.25 mm  
 Insulation material: Polyvinyl Chloride (PVC)  
 Insulation O.D.: 0.10 in. (2.60 mm)  
 Insulation color: Red, Black, White, Green

### JACKET

Material: Polyvinyl Chloride (PVC)  
 Thickness: 0.03 in. (0.80 mm)  
 O.D.: 0.31 in. (8.00 mm)  
 Marking: VERTICAL 4002107 c(ETL)usAUDIO CABLE 14AWG 4 COND 41 STRANDED OXYGEN FREE CMR FT4 CL3R RoHS XXXFT 36011M0601203

### MECHANICAL

Temperature rating: 75° C  
 Before Tensile Strength (Mpa): ≥13.8  
 Aging Elongation (%): ≥100  
 Aging Condition (°Cxhrs): 100x168  
 After Tensile Strength (Mpa): ≥85% of unaged  
 Aging Elongation (%): ≥50% of unaged  
 Cold Bend (-20±2° Cx4hrs): No Crack

### SAFETY



NFPA 70 (NEC®) rating: CMR/CL3  
 Voltage rating: 300 V RMS

### PACKED WEIGHT

209-2321: 39 lb (17.7 kg)  
 209-2321/BK: 39 lb (17.7 kg)  
 209-2321/PR: 38 lb (17.2 kg)

## APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications



## VERTICAL CABLE

951.696.7772 California  
 800.749.2447 Florida  
 845.391.8318 New York



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 11/2023  
 Subject to change without notice.