

DESCRIPTION

14 AWG 2 Conductor Stranded Bare Copper, Unshielded with an overall jacket.

APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications



AUDIO CABLE14 AWG 2 CONDUCTOR STRANDED CABLE

209-2322

Part Number:	Description:
209-2322	Audio Cable, Stranded, Unshielded, 14 AWG 2 C, White 1000 ft.

CONSTRUCTION

Conductor count: 2
Shape: Round
Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 14 AWG Stranding: 41/0.25 mm

Insulation material: Polyvinyl Chloride (PVC) Insulation O.D.: 0.10 in. (2.60 mm)

Insulation color: Red, Black

JACKET

Material: Polyvinyl Chloride (PVC)
Thickness: 0.02 in. (0.60 mm)
O.D.: 0.25 in. (6.40 mm)

Marking: VERTICAL 4001453 c(ETL)us AUDIO CABLE 14AWG 2 COND 65 STRANDED OXYGEN FREE CMR FT4 CL3 RoHS XXXXFT 06607M0221102

MECHANICAL

Temperature rating: 75° C
Before Tensile Strength (Mpa): ≥13.8
Aging Elongation (%): ≥100
Aging Condition (°Cxhrs): 100x168

After Tensile Strength (Mpa): ≥85% of unaged Aging Elongation (%): ≥50% of unaged


Cold Bend (-20±2° Cx4hrs): No Crack

SAFETY

NFPA 70 (NEC®) rating: CMR/CL3
Voltage rating: 300 V RMS

PACKED WEIGHT

209-2322: 44 lb (20 kg)







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York

www.verticalcable.com