

DESCRIPTION

18 AWG 2 Conductor Stranded Bare Copper, Unshielded with an overall jacket.

APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications



AUDIO CABLE18 AWG 2 CONDUCTOR STRANDED CABLE

209-2327

| Part Number: | Description: |
|--------------|---|
| 209-2327 | Audio Cable, Stranded, Unshielded, 18 AWG 2 C, White 1000 ft. |

CONSTRUCTION

Conductor count: 2
Shape: Round
Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: 18 AWG Stranding: 16/0.24 mm

Insulation material: Polyvinyl Chloride (PVC)
Insulation O.D.: 0.07 in. (1.75 mm)

Insulation color: Red, Black

JACKET

Material: Polyvinyl Chloride (PVC)
Thickness: 0.02 in. (0.50 mm)
O.D.: 0.19 in. (4.80 mm)

Marking: VERTICAL 4002107 c(ETL)us AUDIO CABLE 18AWG 2 COND 16 STRANDED OXYGEN FREE CMR FT4 CL3R RoHS XXXXFT

MECHANICAL

Temperature rating: 75° C
Before Tensile Strength (Mpa): ≥13.8
Aging Elongation (%): ≥100
Aging Condition (°Cxhrs): 100x168


After Tensile Strength (Mpa): ≥85% of unaged Aging Elongation (%): ≥50% of unaged Cold Bend (-20±2° Cx4hrs): No Crack

SAFETY

NFPA 70 (NEC®) rating: CMR/CL3 Voltage rating: 300 V RMS

PACKED WEIGHT

209-2327: 23 lb (10.4 kg)







951.696.7772 California 800.749.2447 Florida 845.391.8318 New York