

# RG6 F-TYPE CONNECTOR FOR STANDARD SHIELD PLENUM COAX CABLE



## DESCRIPTION

RG6 Compression F-Type Connector.  
Compatible with RG6 Standard Shield Plenum  
Coax Cable.

## FEATURES

- F-Type Male connector for Standard Shield RG6 Plenum Coax Cable.
- Green plastic identifier ring.
- 25 per pack (Can be bought Individually)
- Suitable Applications: CCTV, Security Cameras, Video.

## TOOLS



Compression/Crimping Tool  
078-1018

## 083-1041/PCP/S

### PHYSICAL SPECIFICATIONS

Body Material:	Brass Nickel Plated
Connector Type:	F-Type Male Coax
Style:	Compression Snap-N-Seal
Color Code:	Green
Outer Diameter:	0.43 in. (11 mm)
RG6 Inner Diameter:	0.31 in. (8 mm)

### MECHANICAL

Nom Impedance:	75 Ohm
Return Loss:	DC-1 GHz 31 dB Return Loss 1.05 VSWR DC-2 GHz 26 dB Return Loss 1.09 VSWR DC-3 GHz 21 dB Return Loss 1.18 VSWR
Locking:	No
Cable Pullout Force:	≥ 40 lb (18 kg)

### CABLE SIZE LIMITS

Conductor Diameter:	0.040 in. - 0.042 in. (1.02 mm - 1.07 mm)
Dielectric Diameter:	0.166 in. - 0.172 in. (4.19 mm - 4.37 mm)
Outer Jacket Diameter:	0.220 in. - 0.250 in. (5.59 mm - 6.35 mm)

### WEIGHT

0.05 lb (0.0226 kg)



**VERTICAL CABLE**

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York

[www.verticalcable.com](http://www.verticalcable.com)

Rev. 1/2024

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.