

# RG6 TWIST-ON CONNECTOR F-TYPE FOR STANDARD-SHIELD COAX CABLE



## DESCRIPTION

RG6 Twist-On F-Type Connector.  
Compatible with RG6 Standard-Shield Coax Cable.

## FEATURES

- F-Type Male connector for RG6 Standard-Shield Coax Cable.
- 100 per pack (Can be bought Individually)
- Suitable Applications: CCTV, Security Cameras, Video.

## TOOLS



Compression/Crimping Tool  
078-1018

## 083-1041/S

### PHYSICAL SPECIFICATIONS

Body Material:	Brass Nickel Plated
Connector Type:	F-Type Male Coax
Style:	Standard-Shield Twist-On
Outer Diameter:	0.43 in. (11 mm)
RG6 Inner Diameter:	0.31 in. (8 mm)

### MECHANICAL

Nom Impedance:	75 Ohm
Return Loss:	DC-1 GHz 31 dB Return Loss 1.05 VSWR DC-2 GHz 26 dB Return Loss 1.09 VSWR DC-3 GHz 21 dB Return Loss 1.18 VSWR
Locking:	No
Cable Pullout Force:	≥ 40 lb (18 kg)

### CABLE SIZE LIMITS

Conductor Diameter:	0.040 in. - 0.042 in. (1.02 mm - 1.07 mm)
Dielectric Diameter:	0.166 in. - 0.193 in. (4.19 mm - 4.90 mm)
Outer Jacket Diameter:	0.230 in. - 0.281 in. (5.84 mm - 7.14 mm)

### WEIGHT

0.05 lb (0.0226 kg)



**VERTICAL CABLE**

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York

[www.verticalcable.com](http://www.verticalcable.com)

Rev. 1/2024

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.