

# DIRECT BURIAL AUDIO CABLE

## 12 AWG 2 CONDUCTOR

### CMX (UV) RATED



## DESCRIPTION

12 AWG 2 Conductor Direct Burial, CMX (UV) Stranded Bare Copper, Unshielded with an overall jacket.

## APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications
- Suitable for Direct Burial
- Durable Weather Resistant Jacket
- UV Rated Outer Jacket



## 209-2324/DB

Part Number:	Description:
209-2324/DB	Audio Cable, Stranded, Unshielded, 12 AWG 2 C, Black 500 ft.

### CONSTRUCTION

Conductor count:	2
Shape:	Round
Rip cord:	Yes
Water Block Tape:	Yes

### CONDUCTORS

Material:	Stranded bare copper
Trade size:	12 AWG
Stranding:	65/0.25 mm
Insulation material:	Polyvinyl Chloride (PVC)
Insulation O.D.:	0.13 in. (3.30 mm)
Insulation color:	Red, Black

### JACKET

Material:	Polyethylene (PE)
Thickness:	0.02 in. (0.55 mm)
O.D.:	0.36 in. (9.20 mm)
Marking:	VERTICAL 4002107 c(ETL)us AUDIO CABLE 12AWG 2 COND 105 STRANDED OXYGEN FREE OUTDOOR UV DIRECT BURIAL RoHS XXXFT

### MECHANICAL


Temperature rating:	75° C
Before Tensile Strength (Mpa):	≥13.8
Aging Elongation (%):	≥100
Aging Condition (°Cxhrs):	100x168
After Tensile Strength (Mpa):	≥85% of unaged
Aging Elongation (%):	≥50% of unaged
Cold Bend (-20±2° Cx4hrs):	No Crack

### SAFETY

NFPA 70 (NEC®) rating:	CMX (UV)
Voltage rating:	300 V RMS

### PACKED WEIGHT

209-2324/DB:	35 lb (15.8 kg)
--------------	-----------------



## VERTICAL CABLE

951.696.7772 California  
 800.749.2447 Florida  
 845.391.8318 New York  
 713.322.7242 Texas



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 3/2024  
 Subject to change without notice.